



Membrane box M1 CEE

- **Membrane technology with conduit grip**
 - » Toolless combination insertion M20 - M32
 - » Insertion of cables is possible
 - » Concrete-tight
 - » Integrated strain relief
 - » No rework - cutting conduits not necessary
- **IP 44 sealing ring**
 - » Combination with cover and sealing ring guarantees protection class IP 44
- **Attachable wings**
 - » For fastening the box to steel reinforcements
 - » Standard spacing of 15 cm to door shuttering
 - » No counter bearing oder support element necessary
 - » For concrete coverings of 20 - 60 mm

Product features

Shape	Octagonal
Length	110 mm
Wide	80 mm
Depth	85 mm
Installation opening	70 mm
Wingspan	300 mm
Colour	Anthracite-orange
Type of insertions	Cables and conduits
Combined insertions with strain relief	2x M15; 4xM15/M20/M25 2x M15/M20/M25/M32
insertions from the back without strain relief	2 x M15/M20/M25 2 x M12
Integrated strain relief	Yes
Stackable	Yes
Screw bosses	4
Sound protection	No
Airtight	Yes
Thermal bridge free	No
Cable transition	Fully insulated
Concrete cover	20-40 mm or 40-60 mm
Counter bearing necessary?	No
Concrete-tight	Yes
Temperature resistant	- 5 to +100 °C

Series	M-series
Article No.	P953
Category	Concrete installation
Type of installation	Wings, glue, magnet, nails
Use	cast-in-place concrete, prefabrication
EAN	4260182066713

Material properties

Housing material	PP
Membrane material	TPE